

## TEKNISET OMINAISUUDET- ETULINGOT

Malli Art. nr. THS Art. nr. H	F130THS/H 15623H/15623V 15624	F150THS/H 14902H/14902V 14903	F180THS/H 14904H/14904V 15308	F160THS/H PRO 17564/17565 15921	F180H PRO 25926	F200THS/H PRO 14906/16931 15938	F220THS/H PRO 17096/17096V 16365	F240H MONSTER 24000	F280H MONSTER 26000
<b>Työskentelyleveys</b>	130 cm	150 cm	180 cm	160 cm	180 cm	200 cm	220 cm	240 cm	280 cm
<b>Heittosiivikon halkaisija</b>	42 cm	42 cm	42 cm	55 cm	55 cm	55 cm	55 cm	95 cm	95 cm
<b>Syöttöruuvi</b>	50 cm	50 cm	50 cm	65 cm	65 cm	65 cm	65 cm	100 cm	100 cm
<b>Paino</b>	240 kg	260 kg	280 kg	520 kg	353 kg	550 kg	610 kg	1340 kg	1470 kg
<b>Voiman tarve (THS)</b>	25 - 45 hp	25 - 45 hp	25 - 45 hp	40 - 70 hp	40 - 70 hp	40 - 70 hp	40 - 70 hp	-	-
<b>PTO rpm (THS)</b>	540, 1000, 2000, 2500 rpm			540, 1000, 2000, 2500 rpm			-	-	-
<b>Öljyn tarve (H)</b>	55-75 l/min - 180-210 bar			100-180 l/min - 190-350 bar	90-180 l/min - 200 bar	100-180 l/min - 190-350 bar	100-180 l/min - 190-350 bar	noin 180l/min - 200 bar	noin 180l/min - 200 bar
<b>Spooriakseli (THS)</b>	1 3/8"	1 3/8"	1 3/8"	1 3/4"	1 3/4"	1 3/4"	1 3/4"	-	-
<b>Kiinnike</b>	Flexi kiinnikkeet**			Flexi kiinnikkeet**			Volvo-BM*	Volvo BM*	
<b>Työkone</b>	1- 3 t.	1- 3 t.	1- 3 t.	3 - 6 t.	3 - 6 t.	3 - 6 t.	3 - 6 t.	7 - 10 t.	10 - 17 t.

\* Kiinnike Trima/SMS on saatavilla valinnaisena varusteena

\*\* Flexi kiinnikkeet ovat saatavilla useimpiin työkoneisiin